

AGRICULTURE

Protective Coatings for Farm Equipment and Implements





Advanced Coatings for your Agricultural Investment

Protective coatings for tractors, farm implements and other equipment require a unique blend of high corrosion resistance and durability. Baril coatings is pleased to offer one of the industry's most dynamic selections of high performance OEM compliant coatings for the agricultural industry.

In addition to traditional epoxy/urethanes, Baril's patented Dual-Cure™ coating systems designed for outstanding performance and efficiency. This patented line of primers, top-coats and single-coat direct to metal systems ensures the longevity of your agricultural investment by providing superior corrosion resistance, flexibility and abrasion resistance. In addition, Dual-Cure™ systems are designed to dry in as little as one hour with no heat required.

Baril strives to work along-side our customers in offering the latest cutting edge protective coating technology. Our products are backed by an industry leading service commitment and a team of veteran coating professionals committed to providing your organization with the most effective coating solution.



Product Benefits

- Industry leading flexibility and chip resistance
- Superior color and gloss retention
- High corrosion resistance
- Efficient two-coat or single coat direct to metal process available
- Dry to touch in 30 minutes, dry to handle in as little as 1-hour



Material Performance

	Accelerated Weathering ISO 11507 ASTM G154	Florida Black Box Exposure	Impact (Direct & Indirect) ASTM D-2794	Chemical Resistance	Salt Spray ASTM B-117	Flexibility: ISO 1519 ASTM D522
DualCure 306 Primer DualCure 174 Topcoat	2500 hrs, Gloss Retention >80%	Pass 48 Months <20% gloss loss	160 in lbs Direct/Indirect	Excellent	Pass 9600 hrs	10 mm ISO 1520 cupping 5-7 mm
DualCure 200 Primer DualCure 174 Topcoat	2500 hrs, Gloss Retention >80%	Pass 48 Months <20% gloss loss	160 in lbs Direct/Indirect	Excellent	Pass 2200 hrs	10 mm ISO 1520 cupping 5-7 mm
SteelKote 825 Primer SteelKote 157 Topcoat	2000 hrs, Gloss Retention >80%	N/A	80 Direct 30 Indirect	Excellent	Pass 1500 hrs	Passes 1/4" Mandrel
SteelKote 825 Primer SteelKote 160 Topcoat	2500 hrs, Gloss Retention >80%	Pass 36 Months <20% gloss loss	80 Direct 30 Indirect	Excellent	Pass 1500 hrs	Passes 1/4" Mandrel
Bariline 700 Primer Bariline 710 Topcoat	825 hrs, Gloss Retention >70%	N/A	40 Direct 15 Indirect	Fair	Pass 500 hrs	Passes 1/4" Mandrel
DualCure 180 DTM Topcoat	2000 hrs, Gloss Retention >80%	N/A	100 Direct 100 Indirect	Fair	Pass 250 hrs	Passes 1/4" Mandrel

This document contains general information only and does not represent any warranties, expressed or implied. Please contact your local Baril Coatings representative for more information. ColorLinks™, FleetSpec™ and the Baril logo are all registered trademarks of Baril Coatings, USA. © 2018 Baril Coatings, USA

