

## 1 Identification

- **Product identifier**
- **Trade name:** *Dual Cure 178 Semi Gloss Polyaspartic Illuminated White*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 Baril Coatings USA, LLC  
 401 Growth Parkway  
 Angola, IN 46703
- **Information department:** Product safety department
- **Emergency telephone number:** During normal opening times: +1 (260) 665-8431

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

titanium dioxide

Quartz (SiO<sub>2</sub>)

- **Hazard statements**

Flammable liquid and vapor.

May cause an allergic skin reaction.

(Contd. on page 2)

**Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White**

(Contd. of page 1)

May cause cancer.

**Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:****NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

**HMIS-ratings (scale 0 - 4)**

Health = \*2

Fire = 3

Reactivity = 0

**Other hazards****Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**3 Composition/information on ingredients****Chemical characterization: Mixtures**

**Description:** Hazardous substances listed below.

**Dangerous components:**

7727-43-7	barium sulphate, natural	>10-≤25%
628-63-7	pentyl acetate	>10-≤25%
136210-30-5	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	>10-≤25%
13463-67-7	titanium dioxide	>10-≤25%
624-41-9	2-methylbutyl acetat	>2.5-≤10%

(Contd. on page 3)

Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White

(Contd. of page 2)

108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
14808-60-7	Quartz (SiO <sub>2</sub> )	0.1-≤2.5%

#### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

7727-43-7	barium sulphate, natural	15 mg/m <sup>3</sup>
628-63-7	pentyl acetate	100 ppm
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
7779-90-0	trizinc bis(orthophosphate)	12 mg/m <sup>3</sup>

(Contd. on page 4)

**Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White**

(Contd. of page 3)

1314-13-2	zinc oxide	10 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1344-28-1	aluminium oxide	15 mg/m <sup>3</sup>
110-43-0	Methyl n-amyl ketone	150 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	14 mg/m <sup>3</sup>
546-93-0	Magnesite	45 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	5 ppm

**· PAC-2:**

7727-43-7	barium sulphate, natural	170 mg/m <sup>3</sup>
628-63-7	pentyl acetate	670 ppm
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
7779-90-0	trizinc bis(orthophosphate)	36 mg/m <sup>3</sup>
1314-13-2	zinc oxide	15 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1344-28-1	aluminium oxide	170 mg/m <sup>3</sup>
110-43-0	Methyl n-amyl ketone	670 ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	110 mg/m <sup>3</sup>
546-93-0	Magnesite	260 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	200 ppm

**· PAC-3:**

7727-43-7	barium sulphate, natural	990 mg/m <sup>3</sup>
628-63-7	pentyl acetate	4000* ppm
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
7779-90-0	trizinc bis(orthophosphate)	220 mg/m <sup>3</sup>
1314-13-2	zinc oxide	2,500 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1344-28-1	aluminium oxide	990 mg/m <sup>3</sup>
110-43-0	Methyl n-amyl ketone	4000* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	680 mg/m <sup>3</sup>
546-93-0	Magnesite	1,600 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	3000* ppm

**7 Handling and storage****· Handling:****· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

(Contd. on page 5)

US

Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White

(Contd. of page 4)

- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

<b>7727-43-7 barium sulphate, natural</b>	
PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 5* mg/m <sup>3</sup> *inhalable fraction; E
<b>628-63-7 pentyl acetate</b>	
PEL	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 532 mg/m <sup>3</sup> , 100 ppm Long-term value: 266 mg/m <sup>3</sup> , 50 ppm
<b>624-41-9 2-methylbutyl acetat</b>	
TLV	Short-term value: 532 mg/m <sup>3</sup> , 100 ppm Long-term value: 266 mg/m <sup>3</sup> , 50 ppm
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
WEEL	Long-term value: 50 ppm
<b>14808-60-7 Quartz (SiO<sub>2</sub>)</b>	
PEL	Long-term value: 0.05* mg/m <sup>3</sup> *resp. dust; 30mg/m <sup>3</sup> /%SiO <sub>2</sub> +2
REL	Long-term value: 0.05* mg/m <sup>3</sup> *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m <sup>3</sup> *as respirable fraction

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.

(Contd. on page 6)

**Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White**

(Contd. of page 5)

· **Breathing equipment:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*

· **Protection of hands:**

Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

· **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

· **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

· **Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties**· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· <b>Form:</b>	Liquid
· <b>Color:</b>	White
· <b>Odor:</b>	Solvent-like
· <b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	138 °C (280.4 °F)

· **Flash point:** 23 °C (73.4 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 375 °C (707 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Contd. on page 7)

**Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White**

(Contd. of page 6)

· <b>Explosion limits:</b>	
<b>Lower:</b>	1 Vol %
<b>Upper:</b>	7.5 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	5.3 hPa (4 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.68 g/cm <sup>3</sup> (14.02 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Miscible
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	22.4 %
<b>VOC content:</b>	22.35 %
	375.5 g/l / 3.13 lb/gal
<b>Solids content:</b>	77.7 % (by weight)
· <b>Other information:</b>	No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>7779-90-0 trizinc bis(orthophosphate)</b>		
Oral	LD50	>5,000 mg/kg (rat)
<b>1314-13-2 zinc oxide</b>		
Oral	LD50	>5,000 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 8)

-US-

**Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White**

(Contd. of page 7)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	3
13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide, chemically prepared	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **Additional ecological information:**· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

**13 Disposal considerations**· **Waste treatment methods**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.





US

(Contd. on page 9)

Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White

(Contd. of page 8)

**14 Transport information**

<ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>	UN1263
<ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul>	Paint PAINT (trizinc bis(orthophosphate), zinc oxide), MARINE POLLUTANT PAINT
<ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	3 Flammable liquids 3
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> </ul>	 
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	3 Flammable liquids 3
<ul style="list-style-type: none"> <li>· <b>IATA</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	3 Flammable liquids 3
<ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>	III
<ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>	Symbol (fish and tree)
<ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Danger code (Kemler):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul>	Warning: Flammable liquids 30 F-E, S-E A
<ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> <li>· <b>DOT</b></li> <li>· <b>Quantity limitations</b></li> </ul>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L

(Contd. on page 10)

US

Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White

(Contd. of page 9)

· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### · Section 313 (Specific toxic chemical listings):

7727-43-7	barium sulphate, natural
7779-90-0	trizinc bis(orthophosphate)
1314-13-2	zinc oxide
1344-28-1	aluminium oxide

### · TSCA (Toxic Substances Control Act):

All ingredients are listed.

### · Proposition 65

#### · Chemicals known to cause cancer:

13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO <sub>2</sub> )

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

#### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

#### · Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

### · Carcinogenic categories

#### · EPA (Environmental Protection Agency)

7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
7779-90-0	trizinc bis(orthophosphate)	D, I, II
1314-13-2	zinc oxide	D, I, II

#### · TLV (Threshold Limit Value established by ACGIH)

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	A4
13463-67-7	titanium dioxide	A4
1344-28-1	aluminium oxide	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
1314-23-4	zirconium dioxide	A4

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	titanium dioxide
------------	------------------

(Contd. on page 11)

**Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White**

(Contd. of page 10)

14808-60-7 | Quartz (SiO<sub>2</sub>)· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate  
titanium dioxide  
Quartz (SiO<sub>2</sub>)

· **Hazard statements**

Flammable liquid and vapor.  
May cause an allergic skin reaction.  
May cause cancer.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If exposed or concerned: Get medical advice/attention.  
Specific treatment (see on this label).  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Mr. Williams

· **Date of preparation / last revision** 08/22/2025 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 12)

US

Printing date 08/22/2025

Reviewed on 08/22/2025

**Trade name: Dual Cure 178 Semi Gloss Polyaspartic Illuminated White**

(Contd. of page 11)

DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Flam. Liq. 3: Flammable liquids – Category 3  
Skin Sens. 1: Skin sensitisation – Category 1  
Carc. 1A: Carcinogenicity – Category 1A

US