

## 1 Identification

- **Product identifier**
- **Trade name:** Dual Cure 183 Semi Gloss DTM Greens
- **Article number:** 183GXXX
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Baril Coatings USA, LLC  
401 Growth Parkway  
Angola, IN 46703
- **Information department:** Product safety department
- **Emergency telephone number:** During normal opening times: +1 (260) 665-8431

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate  
titanium dioxide  
Quartz (SiO<sub>2</sub>)

**Trade name: Dual Cure 183 Semi Gloss DTM Greens**

(Contd. of page 1)

*Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate***· Hazard statements***Highly flammable liquid and vapor.**Causes serious eye irritation.**May cause an allergic skin reaction.**May cause cancer.***· Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Avoid breathing dust/fume/gas/mist/vapors/spray**Wash thoroughly after handling.**Contaminated work clothing must not be allowed out of the workplace.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**If exposed or concerned: Get medical advice/attention.**Specific treatment (see on this label).**If skin irritation or rash occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**Wash contaminated clothing before reuse.**In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Classification system:****· NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

**· HMIS-ratings (scale 0 - 4)**

Health = \*2

Fire = 3

Reactivity = 0

**· Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

US

(Contd. on page 3)

Trade name: Dual Cure 183 Semi Gloss DTM Greens

(Contd. of page 2)

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Hazardous substances listed below.

- **Dangerous components:**

7727-43-7	barium sulphate, natural	>10-≤25%
136210-30-5	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	>10-≤25%
79-20-9	methyl acetate	>10-<20%
628-63-7	pentyl acetate	>2.5-≤10%
13463-67-7	titanium dioxide	>2.5-≤10%
624-41-9	2-methylbutyl acetat	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
112926-00-8	amorphous silica (silica gel, precipitated silica)	≤2.5%
1333-86-4	Carbon black	0.1-≤2.5%
14808-60-7	Quartz (SiO <sub>2</sub> )	0.1-≤2.5%
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.1-<1%

### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

**Trade name: Dual Cure 183 Semi Gloss DTM Greens**

(Contd. of page 3)

Do not allow to enter sewers/ surface or ground water.

• **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

• **Protective Action Criteria for Chemicals**

• **PAC-1:**

7727-43-7	barium sulphate, natural	15 mg/m <sup>3</sup>
79-20-9	methyl acetate	250 ppm
7779-90-0	trizinc bis(orthophosphate)	12 mg/m <sup>3</sup>
628-63-7	pentyl acetate	100 ppm
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
1314-13-2	zinc oxide	10 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
112926-00-8	amorphous silica (silica gel, precipitated silica)	18 mg/m <sup>3</sup>
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
9002-88-4	Polyethylene low density	16 mg/m <sup>3</sup>
1330-20-7	xylene	130 ppm

• **PAC-2:**

7727-43-7	barium sulphate, natural	170 mg/m <sup>3</sup>
79-20-9	methyl acetate	1,700 ppm
7779-90-0	trizinc bis(orthophosphate)	36 mg/m <sup>3</sup>
628-63-7	pentyl acetate	670 ppm
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
1314-13-2	zinc oxide	15 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
112926-00-8	amorphous silica (silica gel, precipitated silica)	200 mg/m <sup>3</sup>
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
9002-88-4	Polyethylene low density	170 mg/m <sup>3</sup>
1330-20-7	xylene	920* ppm

• **PAC-3:**

7727-43-7	barium sulphate, natural	990 mg/m <sup>3</sup>
79-20-9	methyl acetate	10000* ppm
7779-90-0	trizinc bis(orthophosphate)	220 mg/m <sup>3</sup>
628-63-7	pentyl acetate	4000* ppm
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
1314-13-2	zinc oxide	2,500 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
112926-00-8	amorphous silica (silica gel, precipitated silica)	1,200 mg/m <sup>3</sup>
1333-86-4	Carbon black	590 mg/m <sup>3</sup>

(Contd. on page 5)

**Trade name: Dual Cure 183 Semi Gloss DTM Greens**

		(Contd. of page 4)
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>
9002-88-4	Polyethylene low density	1,000 mg/m <sup>3</sup>
1330-20-7	xylene	2500* ppm

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

<b>7727-43-7 barium sulphate, natural</b>	
PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 5* mg/m <sup>3</sup> *inhalable fraction; E
<b>79-20-9 methyl acetate</b>	
PEL	Long-term value: 610 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 760 mg/m <sup>3</sup> , 250 ppm Long-term value: 610 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 757 mg/m <sup>3</sup> , 250 ppm Long-term value: 606 mg/m <sup>3</sup> , 200 ppm
<b>628-63-7 pentyl acetate</b>	
PEL	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 532 mg/m <sup>3</sup> , 100 ppm Long-term value: 266 mg/m <sup>3</sup> , 50 ppm

(Contd. on page 6)

**Trade name: Dual Cure 183 Semi Gloss DTM Greens**

(Contd. of page 5)

<b>624-41-9 2-methylbutyl acetat</b>	
TLV	Short-term value: 532 mg/m <sup>3</sup> , 100 ppm Long-term value: 266 mg/m <sup>3</sup> , 50 ppm
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
WEEL	Long-term value: 50 ppm
<b>112926-00-8 amorphous silica (silica gel, precipitated silica)</b>	
PEL	20mppcf or 80mg/m <sup>3</sup> /%SiO <sub>2</sub>
REL	Long-term value: 6 mg/m <sup>3</sup> See Pocket Guide App. C
TLV	TLV withdrawn
<b>1333-86-4 Carbon black</b>	
PEL	Long-term value: 3.5 mg/m <sup>3</sup>
REL	Long-term value: 3.5* mg/m <sup>3</sup> *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m <sup>3</sup> *inhalable fraction
<b>14808-60-7 Quartz (SiO<sub>2</sub>)</b>	
PEL	Long-term value: 0.05* mg/m <sup>3</sup> *resp. dust; 30mg/m <sup>3</sup> /%SiO <sub>2</sub> +2
REL	Long-term value: 0.05* mg/m <sup>3</sup> *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m <sup>3</sup> *as respirable fraction

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

Trade name: Dual Cure 183 Semi Gloss DTM Greens

(Contd. of page 6)

## · Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

## · Information on basic physical and chemical properties

## · General Information

## · Appearance:

Form:	Liquid
Color:	Green
Odor:	Solvent-like
Odor threshold:	Not determined.

· pH-value: Not determined.

## · Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	57 °C (134.6 °F)

· Flash point: 10 °C (50 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 375 °C (707 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

## · Explosion limits:

Lower:	3.1 Vol %
Upper:	16 Vol %

· Vapor pressure at 20 °C (68 °F): 220 hPa (165 mm Hg)

· Density at 20 °C (68 °F): 1.58 g/cm<sup>3</sup> (13.19 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

## · Solubility in / Miscibility with

Water: Miscible

· Partition coefficient (n-octanol/water): Not determined.

## · Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

## · Solvent content:

Organic solvents:	14.0 %
VOC content:	14.02 %
	221.5 g/l / 1.85 lb/gal

Solids content: 74.3 % (by weight)

(Contd. on page 8)

Trade name: Dual Cure 183 Semi Gloss DTM Greens

(Contd. of page 7)

· **Other information:** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**7779-90-0 trizinc bis(orthophosphate)**

Oral | LD50 | &gt;5,000 mg/kg (rat)

**1314-13-2 zinc oxide**

Oral | LD50 | &gt;5,000 mg/kg (rat)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

13463-67-7 titanium dioxide 2B

1333-86-4 Carbon black 2B

14808-60-7 Quartz (SiO<sub>2</sub>) 1

9002-88-4 Polyethylene low density 3

1330-20-7 xylene 3

- **NTP (National Toxicology Program)**

14808-60-7 Quartz (SiO<sub>2</sub>) K

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 9)

**Trade name: Dual Cure 183 Semi Gloss DTM Greens**




(Contd. of page 8)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.


**14 Transport information**

· <b>UN-Number</b>	
· <b>DOT, IMDG, IATA</b>	UN1263
· <b>UN proper shipping name</b>	
· <b>DOT</b>	Paint
· <b>IMDG</b>	PAINT (trizinc bis(orthophosphate), zinc oxide), MARINE POLLUTANT
· <b>IATA</b>	PAINT
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>IMDG</b>	
	 
· <b>Class</b>	3 Flammable liquids

(Contd. on page 10)

**Trade name: Dual Cure 183 Semi Gloss DTM Greens**

(Contd. of page 9)

· <b>Label</b>	3
· <b>IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>DOT, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	Product contains environmentally hazardous substances: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
· <b>Marine pollutant:</b>	Symbol (fish and tree)
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Danger code (Kemler):</b>	33
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	B
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

7727-43-7	barium sulphate, natural
7779-90-0	trizinc bis(orthophosphate)
1314-13-2	zinc oxide
1330-20-7	xylene

· **TSCA (Toxic Substances Control Act):**

7727-43-7	barium sulphate, natural
136210-30-5	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

(Contd. on page 11)

**Trade name: Dual Cure 183 Semi Gloss DTM Greens**

(Contd. of page 10)

79-20-9	methyl acetate
7779-90-0	trizinc bis(orthophosphate)
628-63-7	pentyl acetate
13463-67-7	titanium dioxide
1314-13-2	zinc oxide
624-41-9	2-methylbutyl acetat
108-65-6	2-methoxy-1-methylethyl acetate
1333-86-4	Carbon black
623-91-6	diethyl fumarate
104810-47-1	poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-
14808-60-7	Quartz (SiO <sub>2</sub> )
104810-48-2	poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxy-
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate
9002-88-4	Polyethylene low density
1330-20-7	xylene

· **TSCA new (21st Century Act) (Substances not listed)**

112926-00-8 | amorphous silica (silica gel, precipitated silica)

· **Proposition 65**· **Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO <sub>2</sub> )

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
7779-90-0	trizinc bis(orthophosphate)	D, I, II
1314-13-2	zinc oxide	D, I, II
1330-20-7	xylene	I

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	titanium dioxide	A4
1333-86-4	Carbon black	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
1330-20-7	xylene	A4

(Contd. on page 12)

**Trade name: Dual Cure 183 Semi Gloss DTM Greens**

(Contd. of page 11)

· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>	
13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO <sub>2</sub> )

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

tetraethyl-N,N'-(methylenedicyclohexane-4, 1-diyl)bis-DL-aspartate  
titanium dioxide

Quartz (SiO<sub>2</sub>)

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

· **Hazard statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause cancer.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 13)

**Trade name: Dual Cure 183 Semi Gloss DTM Greens**

(Contd. of page 12)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.· **Contact:** Mr. Williams· **Date of preparation / last revision** 08/22/2025 / -· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 1A: Carcinogenicity – Category 1A