

1 Identification

- **Product identifier**
- **Trade name: FleetSpec 1260 Greens**
- **Article number: 1260GXXX**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Baril Coatings USA, LLC
 401 Growth Parkway
 Angola, IN 46703
- **Information department: Product safety department**
- **Emergency telephone number: During normal opening times: +1 (260) 665-8431**

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word Danger**

- **Hazard-determining components of labeling:**

4-methylpentan-2-one

Solvent naphtha (petroleum), light arom.

ethanol

Trade name: FleetSpec 1260 Greens

(Contd. of page 1)

*Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate***Hazard statements***Flammable liquid and vapor.**May cause an allergic skin reaction.**May cause genetic defects.**May cause cancer.***Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Avoid breathing dust/fume/gas/mist/vapors/spray**Contaminated work clothing must not be allowed out of the workplace.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If exposed or concerned: Get medical advice/attention.**Specific treatment (see on this label).**If skin irritation or rash occurs: Get medical advice/attention.**Wash contaminated clothing before reuse.**In case of fire: Use for extinction: CO₂, powder or water spray.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Classification system:****NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = *2

Fire = 3

Reactivity = 0

Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**3 Composition/information on ingredients****Chemical characterization: Mixtures****Description:** Hazardous substances listed below.**Dangerous components:**

123-86-4	<i>n</i> -butyl acetate	>10-<20%
----------	-------------------------	----------

(Contd. on page 3)

Trade name: FleetSpec 1260 Greens

(Contd. of page 2)

110-43-0	Methyl n-amyl ketone	>10-≤25%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
108-10-1	4-methylpentan-2-one	>2.5-<10%
763-69-9	ethyl 3-ethoxypropionate	≤2.5%
1330-20-7	xylene	≤2.5%
13463-67-7	titanium dioxide	0.1-≤2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	0.1-≤2.5%
100-41-4	ethylbenzene	0.1-≤2.5%
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.1-<1%
64-17-5	ethanol	0.1-≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Trade name: FleetSpec 1260 Greens

(Contd. of page 3)

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**· **PAC-1:**

123-86-4	<i>n</i> -butyl acetate	5 ppm
110-43-0	Methyl <i>n</i> -amyl ketone	150 ppm
20344-49-4	iron hydroxide oxide	24 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
108-10-1	4-methylpentan-2-one	75 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
1330-20-7	xylene	130 ppm
13463-67-7	titanium dioxide	30 mg/m ³
628-63-7	pentyl acetate	100 ppm
100-41-4	ethylbenzene	33 ppm
111-76-2	2-butoxyethanol	60 ppm
64-17-5	ethanol	1,800 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm

· **PAC-2:**

123-86-4	<i>n</i> -butyl acetate	200 ppm
110-43-0	Methyl <i>n</i> -amyl ketone	670 ppm
20344-49-4	iron hydroxide oxide	260 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
108-10-1	4-methylpentan-2-one	500 ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
1330-20-7	xylene	920* ppm
13463-67-7	titanium dioxide	330 mg/m ³
628-63-7	pentyl acetate	670 ppm
100-41-4	ethylbenzene	1100* ppm
111-76-2	2-butoxyethanol	120 ppm
64-17-5	ethanol	3300* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm

· **PAC-3:**

123-86-4	<i>n</i> -butyl acetate	3000* ppm
110-43-0	Methyl <i>n</i> -amyl ketone	4000* ppm
20344-49-4	iron hydroxide oxide	1,600 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
1330-20-7	xylene	2500* ppm
13463-67-7	titanium dioxide	2,000 mg/m ³
628-63-7	pentyl acetate	4000* ppm
100-41-4	ethylbenzene	1800* ppm
111-76-2	2-butoxyethanol	700 ppm
64-17-5	ethanol	15000* ppm

(Contd. on page 5)

Trade name: FleetSpec 1260 Greens

108-83-8 | 2,6-dimethylheptan-4-one

(Contd. of page 4)

2000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

110-43-0 Methyl n-amyl ketone

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 233 mg/m ³ , 50 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

108-10-1 4-methylpentan-2-one

PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI

(Contd. on page 6)

Trade name: FleetSpec 1260 Greens

(Contd. of page 5)

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

64-17-5 ethanol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm

Ingredients with biological limit values:**108-10-1 4-methylpentan-2-one**

BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
-----	--

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

100-41-4 ethylbenzene

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 7)

US

Trade name: FleetSpec 1260 Greens

(Contd. of page 6)

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Liquid
Color:	Green
Odor:	Solvent-like
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)

· **Flash point:** 27 °C (80.6 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C (698 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	1 Vol %
Upper:	7.5 Vol %

(Contd. on page 8)

Trade name: FleetSpec 1260 Greens

(Contd. of page 7)

· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	1.1 g/cm ³ (9.18 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Miscible
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	34.7 %
VOC content:	34.69 %
	381.6 g/l / 3.18 lb/gal
· Solids content:	63.3 % (by weight)
· Other information:	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Carcinogenic.
The product can cause inheritable damage.

(Contd. on page 9)

Trade name: FleetSpec 1260 Greens

(Contd. of page 8)

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

108-10-1	4-methylpentan-2-one	2B
1330-20-7	xylene	3
13463-67-7	titanium dioxide	2B
100-41-4	ethylbenzene	2B
111-76-2	2-butoxyethanol	3
64-17-5	ethanol	1

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|--------|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · IMDG, IATA | PAINT |

(Contd. on page 10)

US

Trade name: FleetSpec 1260 Greens

(Contd. of page 9)

· **Transport hazard class(es)**· **DOT**

· **Class** 3 Flammable liquids
 · **Label** 3

· **IMDG, IATA**

· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**

· **DOT, IMDG, IATA** III

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Flammable liquids

· **Danger code (Kemler):** 30

· **EMS Number:** F-E, S-E

· **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 60 L
 On cargo aircraft only: 220 L

· **IMDG**

· **Limited quantities (LQ)** 5L

· **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 · **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-10-1 4-methylpentan-2-one

1330-20-7 xylene

100-41-4 ethylbenzene

(Contd. on page 11)

Printing date 08/18/2025

Reviewed on 08/18/2025

Trade name: FleetSpec 1260 Greens

(Contd. of page 10)

111-76-2 2-butoxyethanol

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

108-10-1 4-methylpentan-2-one

13463-67-7 titanium dioxide

100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-10-1 4-methylpentan-2-one

64-17-5 ethanol

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

108-10-1 4-methylpentan-2-one

I

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

111-76-2 2-butoxyethanol

NL

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7 xylene

A4

13463-67-7 titanium dioxide

A4

100-41-4 ethylbenzene

A3

111-76-2 2-butoxyethanol

A3

64-17-5 ethanol

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word Danger**· **Hazard-determining components of labeling:**

4-methylpentan-2-one

Solvent naphtha (petroleum), light arom.

ethanol

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

· **Hazard statements**

Flammable liquid and vapor.

May cause an allergic skin reaction.

(Contd. on page 12)

Trade name: FleetSpec 1260 Greens

(Contd. of page 11)

May cause genetic defects.

May cause cancer.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:**Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environment protection department.

Contact: Mr. Williams

Date of preparation / last revision 08/18/2025 / -

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 13)

Printing date 08/18/2025

Reviewed on 08/18/2025

Trade name: FleetSpec 1260 Greens

(Contd. of page 12)

PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 3: Flammable liquids – Category 3
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1A: Carcinogenicity – Category 1A

US