

## 1 Identification

- **Product identifier**
- **Trade name: Steelkote 154 High Gloss Grays & Beiges**
- **Article number: 154GBXXX**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Baril Coatings USA, LLC  
401 Growth Parkway  
Angola, IN 46703
- **Information department: Product safety department**
- **Emergency telephone number: During normal opening times: +1 (260) 665-8431**

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word Danger**

**Trade name: Steelkote 154 High Gloss Grays & Beiges**

(Contd. of page 1)

**· Hazard-determining components of labeling:**

titanium dioxide  
Stoddard solvent  
ethylbenzene  
ethanol  
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

**· Hazard statements**

Flammable liquid and vapor.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
May cause genetic defects.  
May cause cancer.  
May cause damage to the hearing organs through prolonged or repeated exposure.

**· Precautionary statements**

If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If exposed or concerned: Get medical advice/attention.  
Specific treatment (see on this label).  
Get medical advice/attention if you feel unwell.  
Take off contaminated clothing and wash it before reuse.  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Classification system:****· NFPA ratings (scale 0 - 4)****· HMIS-ratings (scale 0 - 4)**

(Contd. on page 3)

Printing date 08/19/2025

Reviewed on 08/19/2025

Trade name: **Steelkote 154 High Gloss Grays & Beiges**

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Hazardous substances listed below.

- **Dangerous components:**

110-43-0	Methyl n-amyl ketone	>10-≤25%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>10-≤25%
13463-67-7	titanium dioxide	>2.5-≤10%
123-86-4	n-butyl acetate	>2.5-≤10%
1330-20-7	xylene	≤2.5%
100-41-4	ethylbenzene	0.1-≤2.5%
8052-41-3	Stoddard solvent	0.1-≤2.5%
64-17-5	ethanol	0.1-≤2.5%
1333-86-4	Carbon black	0.1-≤2.5%
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.1-<1%

### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

US

**Trade name: Steelkote 154 High Gloss Grays & Beiges**

(Contd. of page 3)

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**· **PAC-1:**

110-43-0	Methyl n-amyl ketone	150 ppm
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
628-63-7	pentyl acetate	100 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1344-28-1	aluminium oxide	15 mg/m <sup>3</sup>
20344-49-4	iron hydroxide oxide	24 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	300 mg/m <sup>3</sup>
64-17-5	ethanol	1,800 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	14 mg/m <sup>3</sup>
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
67-56-1	methanol	530 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>

· **PAC-2:**

110-43-0	Methyl n-amyl ketone	670 ppm
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
628-63-7	pentyl acetate	670 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1344-28-1	aluminium oxide	170 mg/m <sup>3</sup>
20344-49-4	iron hydroxide oxide	260 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	1,800 mg/m <sup>3</sup>
64-17-5	ethanol	3300* ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	110 mg/m <sup>3</sup>
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
67-56-1	methanol	2,100 ppm

(Contd. on page 5)

**Trade name: Steelkote 154 High Gloss Grays & Beiges**

		(Contd. of page 4)
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
<b>· PAC-3:</b>		
110-43-0	Methyl n-amyl ketone	4000* ppm
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
628-63-7	pentyl acetate	4000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1344-28-1	aluminium oxide	990 mg/m <sup>3</sup>
20344-49-4	iron hydroxide oxide	1,600 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	29500** mg/m <sup>3</sup>
64-17-5	ethanol	15000* ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	680 mg/m <sup>3</sup>
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
67-56-1	methanol	7200* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

**110-43-0 Methyl n-amyl ketone**

PEL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
-----	--

(Contd. on page 6)

**Trade name: Steelkote 154 High Gloss Grays & Beiges**

(Contd. of page 5)

REL Long-term value: 465 mg/m<sup>3</sup>, 100 ppmTLV Long-term value: 233 mg/m<sup>3</sup>, 50 ppm**123-86-4 n-butyl acetate**PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppmREL Short-term value: 950 mg/m<sup>3</sup>, 200 ppmLong-term value: 710 mg/m<sup>3</sup>, 150 ppmTLV Short-term value: 712 mg/m<sup>3</sup>, 150 ppmLong-term value: 238 mg/m<sup>3</sup>, 50 ppm**1330-20-7 xylene**PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL Short-term value: 655 mg/m<sup>3</sup>, 150 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppmTLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppmLong-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

**100-41-4 ethylbenzene**PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL Short-term value: 545 mg/m<sup>3</sup>, 125 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppmTLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm

BEI

**8052-41-3 Stoddard solvent**PEL Long-term value: 2900 mg/m<sup>3</sup>, 500 ppmREL Long-term value: 350 mg/m<sup>3</sup>Ceiling limit value: 1800\* mg/m<sup>3</sup>

\*15-min

TLV Long-term value: 525 mg/m<sup>3</sup>, 100 ppm**64-17-5 ethanol**PEL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppmREL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppmTLV Short-term value: 1880 mg/m<sup>3</sup>, 1000 ppm**1333-86-4 Carbon black**PEL Long-term value: 3.5 mg/m<sup>3</sup>REL Long-term value: 3.5\* mg/m<sup>3</sup>

\*0.1 in presence of PAHs; See Pocket Guide Apps.A+C

TLV Long-term value: 3\* mg/m<sup>3</sup>

\*inhalable fraction

**· Ingredients with biological limit values:****1330-20-7 xylene**

BEI 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

(Contd. on page 7)

**Trade name: Steelkote 154 High Gloss Grays & Beiges**

(Contd. of page 6)

**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**  
**Form:** Liquid

(Contd. on page 8)

US

**Trade name: Steelkote 154 High Gloss Grays & Beiges**

(Contd. of page 7)

· <b>Color:</b>	Grey
· <b>Odor:</b>	Solvent-like
· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	124-128 °C (255.2-262.4 °F)
· <b>Flash point:</b>	27 °C (80.6 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	370 °C (698 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1 Vol %
<b>Upper:</b>	5.5 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	3.5 hPa (2.6 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.13 g/cm <sup>3</sup> (9.43 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Miscible
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	29.7 %
<b>VOC content:</b>	29.66 %
	335.2 g/l / 2.80 lb/gal
· <b>Solids content:</b>	56.9 % (by weight)
· <b>Other information:</b>	No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 9)

Trade name: **Steelkote 154 High Gloss Grays & Beiges**

(Contd. of page 8)

· **Hazardous decomposition products:** No dangerous decomposition products known.**11 Toxicological information**· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****110-43-0 Methyl n-amyl ketone**

Oral	LD50	1,670 mg/kg (rat)
Dermal	LD50	12,600 mg/kg (rabbit)

· **Primary irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** No irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Carcinogenic.

The product can cause inheritable damage.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1
1333-86-4	Carbon black	2B
7631-86-9	silicon dioxide, chemically prepared	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

(Contd. on page 10)

Printing date 08/19/2025

Reviewed on 08/19/2025

Trade name: **Steelkote 154 High Gloss Grays & Beiges**



(Contd. of page 9)

- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |   |                            |
|---|----------------------------|
| · <b>UN-Number</b>  |                            |
| · <b>DOT, IMDG, IATA</b>  | UN1263                     |
| · <b>UN proper shipping name</b>  |                            |
| · <b>DOT</b>  | Paint                      |
| · <b>IMDG, IATA</b>   | PAINT                      |
| · <b>Transport hazard class(es)</b>   |                            |
| · <b>DOT</b>  |                            |
|   |                            |
| · <b>Class</b>  | 3 Flammable liquids        |
| · <b>Label</b>  | 3                          |
| · <b>IMDG, IATA</b>   |                            |
|  |                            |
| · <b>Class</b>  | 3 Flammable liquids        |
| · <b>Label</b>  | 3                          |
| · <b>Packing group</b>  |                            |
| · <b>DOT, IMDG, IATA</b>  | III                        |
| · <b>Environmental hazards:</b>   | Not applicable.            |
| · <b>Special precautions for user</b>   | Warning: Flammable liquids |
| · <b>Danger code (Kemler):</b>  | 30                         |
| · <b>EMS Number:</b>  | F-E, S-E                   |
| · <b>Stowage Category</b>   | A                          |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>    | Not applicable.            |

(Contd. on page 11)

US

Printing date 08/19/2025

Reviewed on 08/19/2025

Trade name: Steelkote 154 High Gloss Grays &amp; Beiges

(Contd. of page 10)

· **Transport/Additional information:**· **DOT**· **Quantity limitations**

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· **IMDG**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III

**15 Regulatory information**· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 | xylene

100-41-4 | ethylbenzene

1344-28-1 | aluminium oxide

67-56-1 | methanol

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

13463-67-7 | titanium dioxide

100-41-4 | ethylbenzene

1333-86-4 | Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5 | ethanol

67-56-1 | methanol

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

1330-20-7 | xylene

I

100-41-4 | ethylbenzene

D

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7 | titanium dioxide

A4

1330-20-7 | xylene

A4

(Contd. on page 12)

**Trade name: Steelkote 154 High Gloss Grays & Beiges**

(Contd. of page 11)

100-41-4	ethylbenzene	A3
1344-28-1	aluminium oxide	A4
64-17-5	ethanol	A3
1314-23-4	zirconium dioxide	A4
1333-86-4	Carbon black	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

titanium dioxide

Stoddard solvent

ethylbenzene

ethanol

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

(Contd. on page 13)

**Trade name: Steelkote 154 High Gloss Grays & Beiges**

(Contd. of page 12)

Get medical advice/attention if you feel unwell.  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** Mr. Williams

- **Date of preparation / last revision** 08/19/2025 / -

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1A: Carcinogenicity – Category 1A

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2