

1 Identification

- **Product identifier**
- **Trade name: Steelkote 157 High Gloss Whites**
- **Article number: 157WXXX**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Baril Coatings USA, LLC
401 Growth Parkway
Angola, IN 46703
- **Information department: Product safety department**
- **Emergency telephone number: During normal opening times: +1 (260) 665-8431**

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

titanium dioxide

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

ethanol

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

(Contd. on page 2)

US

Trade name: Steelkote 157 High Gloss Whites

(Contd. of page 1)

Hazard statements*Flammable liquid and vapor.**May cause an allergic skin reaction.**May cause cancer.***Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Avoid breathing dust/fume/gas/mist/vapors/spray**Contaminated work clothing must not be allowed out of the workplace.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF exposed or concerned: Get medical advice/attention.**Specific treatment (see on this label).**If skin irritation or rash occurs: Get medical advice/attention.**Wash contaminated clothing before reuse.**In case of fire: Use for extinction: CO2, powder or water spray.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Classification system:****NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = *2

Fire = 3

Reactivity = 0

Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**3 Composition/information on ingredients****Chemical characterization: Mixtures****Description:** Hazardous substances listed below.**Dangerous components:**

13463-67-7	titanium dioxide	>10-≤25%
123-86-4	n-butyl acetate	>10-<20%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%

(Contd. on page 3)

Trade name: Steelkote 157 High Gloss Whites

(Contd. of page 2)

110-43-0	Methyl n-amyl ketone	>2.5-≤10%
540-88-5	tert-butyl acetate	≤2.5%
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	1-≤2.5%
100-41-4	ethylbenzene	0.1-≤2.5%
64-17-5	ethanol	0.1-≤2.5%
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.1-<1%

4 First-aid measures· **Description of first aid measures**· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures· **Extinguishing media**· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

6 Accidental release measures· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Trade name: **Steelkote 157 High Gloss Whites**

(Contd. of page 3)

· **Protective Action Criteria for Chemicals**· **PAC-1:**

13463-67-7	titanium dioxide	30 mg/m ³
123-86-4	n-butyl acetate	5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
110-43-0	Methyl n-amyl ketone	150 ppm
540-88-5	tert-butyl acetate	600 ppm
1344-28-1	aluminium oxide	15 mg/m ³
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	90 mg/m ³
1330-20-7	xylene	130 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
100-41-4	ethylbenzene	33 ppm
1314-23-4	zirconium dioxide	14 mg/m ³
628-63-7	pentyl acetate	100 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m ³
64-17-5	ethanol	1,800 ppm
71-36-3	butan-1-ol	60 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm

· **PAC-2:**

13463-67-7	titanium dioxide	330 mg/m ³
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
110-43-0	Methyl n-amyl ketone	670 ppm
540-88-5	tert-butyl acetate	1,700 ppm
1344-28-1	aluminium oxide	170 mg/m ³
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	990 mg/m ³
1330-20-7	xylene	920* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
100-41-4	ethylbenzene	1100* ppm
1314-23-4	zirconium dioxide	110 mg/m ³
628-63-7	pentyl acetate	670 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m ³
64-17-5	ethanol	3300* ppm
71-36-3	butan-1-ol	800 ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm

· **PAC-3:**

13463-67-7	titanium dioxide	2,000 mg/m ³
123-86-4	n-butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
110-43-0	Methyl n-amyl ketone	4000* ppm
540-88-5	tert-butyl acetate	10,000 ppm

(Contd. on page 5)

Trade name: Steelkote 157 High Gloss Whites

		(Contd. of page 4)
1344-28-1	aluminium oxide	990 mg/m ³
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	5,900 mg/m ³
1330-20-7	xylene	2500* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
100-41-4	ethylbenzene	1800* ppm
1314-23-4	zirconium dioxide	680 mg/m ³
628-63-7	pentyl acetate	4000* ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m ³
64-17-5	ethanol	15000* ppm
71-36-3	butan-1-ol	8000** ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm

(Contd. on page 6)

Printing date 08/19/2025

Reviewed on 08/19/2025

Trade name: Steelkote 157 High Gloss Whites

(Contd. of page 5)

110-43-0 Methyl n-amyl ketone

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 233 mg/m ³ , 50 ppm

540-88-5 tert-butyl acetate

PEL	Long-term value: 950 mg/m ³ , 200 ppm
REL	Long-term value: 950 mg/m ³ , 200 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

64-17-5 ethanol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm

· Ingredients with biological limit values:**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 7)

US

Trade name: Steelkote 157 High Gloss Whites

(Contd. of page 6)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Liquid
· Color:	White
· Odor:	Solvent-like
· Odor threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)

· **Flash point:** 27 °C (80.6 °F)· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 315 °C (599 °F)· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.· **Explosion limits:**

· Lower:	1.2 Vol %
· Upper:	7.5 Vol %

· **Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)· **Density at 20 °C (68 °F):** 1.2 g/cm³ (10.01 lbs/gal)· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**· **Water:** Miscible· **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 8)

Printing date 08/19/2025

Reviewed on 08/19/2025

Trade name: **Steelkote 157 High Gloss Whites**

(Contd. of page 7)

- | | |
|-----------------------------|--|
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 31.7 % |
| VOC content: | 31.70 %
380.4 g/l / 3.17 lb/gal |
| · Solids content: | 64.7 % (by weight) |
| · Other information: | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
7631-86-9	silicon dioxide, chemically prepared	3
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

-US

(Contd. on page 9)

Trade name: **Steelkote 157 High Gloss Whites**

(Contd. of page 8)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1263

- **UN proper shipping name**
- **DOT** Paint
- **IMDG, IATA** PAINT

- **Transport hazard class(es)**
- **DOT**




- **Class** 3 Flammable liquids

(Contd. on page 10)

US

Trade name: **Steelkote 157 High Gloss Whites**

(Contd. of page 9)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1344-28-1 aluminium oxide

1330-20-7 xylene

100-41-4 ethylbenzene

71-36-3 butan-1-ol

· TSCA (Toxic Substances Control Act):

13463-67-7 titanium dioxide

123-86-4 n-butyl acetate

108-65-6 2-methoxy-1-methylethyl acetate

110-43-0 Methyl n-amyl ketone

540-88-5 tert-butyl acetate

(Contd. on page 11)

Trade name: Steelkote 157 High Gloss Whites

(Contd. of page 10)

1344-28-1	aluminium oxide
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)
1330-20-7	xylene
7631-86-9	silicon dioxide, chemically prepared
100-41-4	ethylbenzene
1314-23-4	zirconium dioxide
628-63-7	pentyl acetate
104810-47-1	poly(oxy-1,2-ethanediyl), α -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- ω -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane
624-41-9	2-methylbutyl acetat
104810-48-2	poly(oxy-1,2-ethanediyl), α -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- ω -hydroxy-
64-17-5	ethanol
71-36-3	butan-1-ol
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
108-83-8	2,6-dimethylheptan-4-one

· **Proposition 65**· **Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
---------	---------

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
71-36-3	butan-1-ol	D

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	titanium dioxide	A4
1344-28-1	aluminium oxide	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
1314-23-4	zirconium dioxide	A4
64-17-5	ethanol	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
------------	------------------

(Contd. on page 12)

Trade name: Steelkote 157 High Gloss Whites

(Contd. of page 11)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

titanium dioxide

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) ethanol

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

· **Hazard statements**

Flammable liquid and vapor.

May cause an allergic skin reaction.

May cause cancer.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.· **Contact:** Mr. Williams· **Date of preparation / last revision** 08/19/2025 / -· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 13)

Printing date 08/19/2025

Reviewed on 08/19/2025

Trade name: Stealkote 157 High Gloss Whites

(Contd. of page 12)

IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 3: Flammable liquids – Category 3
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 1A: Carcinogenicity – Category 1A

US